



Take your office productivity to a new level.

# Kodak i100 Series Scanners



All the scanning performance and flexibility your busy office or department needs.

- Simplex (i150) and duplex (i160) models for colour, bitonal and greyscale imaging
- Perfect Page Scanning with iThresholding delivers sharp, clean images without rescanning
- Renowned SurePath paper handling that minimises jams
- Scans up to A3-size documents to handle your full workload
- 3-D ultrasonic multi-feed detection lets you scan with confidence
- Easy setup and operation
- Worldwide service and support for your peace of mind



KODAK Capture Software,  
Lite



## Features and Benefits

Perfect Page Scanning with iThresholding: Advanced image processing from Kodak allows you to scan even poor-quality documents and get great images. Image cropping and straightening happen at full scanning speed. We've virtually eliminated the need to rescan or change settings so that you can be more productive, automatically.



Competitive scanner



Perfect Page Scanning with iThresholding, only from Kodak

Exclusive SurePath paper handling is designed for smooth paper transport and virtually jam-free operation.

Flexible feeding capability: Get through workloads faster by scanning documents up to A4 length (297 mm) in landscape mode. For more flexibility, the feeder handles documents up to 432 mm (A3 length) in portrait mode.

Five output options: Colour, bitonal, greyscale, simultaneous bitonal and greyscale and simultaneous bitonal and colour.

Electronic Colour Dropout: Suppress irrelevant red, green or blue backgrounds for efficient forms processing.

3-D multi-feed detection with ultrasonic technology lets you feed a wide variety of paper types and weights with confidence that you'll capture your images.

IEEE-1394 (FIREWIRE) interface allows for quick setup and speeds your images on their way. For your convenience, we also include the IEEE-1394 card and cable.

Small footprint and quiet operation: Both models scan large documents but are still small enough to fit easily on any desktop.

KODAK Capture Software, Lite installs in minutes and supports a range of scanning features for practically any office application. Easily upgradeable to the full version of Capture Software.

VRS Compatible for additional imaging options.


KODAK Service & Support: Our team of service experts is here for you around-the-clock, all over the world.

## Specifications

Recommended Daily Volume	Up to 3,000 pages per day
Throughput Speeds (Landscape, Letter Sized, Bitonal, Greyscale, Colour)	Resolution i150 (simplex) i160 (duplex) 150 dpi 53 ppm/53 ppm/106 ipm 200 dpi 40 ppm/40 ppm/80 ipm 300 dpi 27 ppm/27 ppm/54 ipm Scanning with simultaneous output of bitonal and colour, or bitonal and greyscale, images Resolution i150 (simplex) i160 (duplex) 150 dpi 53 ppm/106 ipm 53 ppm/212 ipm 200 dpi 40 ppm/80 ipm 40 ppm/160 ipm 300 dpi 20 ppm/40 ipm 20 ppm/80 ipm Single Tricolour Plus CCD (i150); Dual Tricolour Plus CCD (i160) Greyscale output bit depth is 256 levels (8-bit) Colour capture bit depth is 40 bit (40 bits per red, green, blue and black channels)
Scanning Technology	Colour output bit depth is 24-bit 300 dpi Single 2500 hour+ Xenon lamps 75/100/150/200/240/300/400/600 dpi 297 mm x 432 mm 64 mm x 89 mm
Optical Resolution	Onionskin to card stock
Illumination	Automatic Document Feeder for continuous loading of up to 150 sheets of 60 g/m <sup>2</sup> paper
Output Resolution	3-D multi-feed detection with ultrasonic technology
Maximum Document Size	IEEE-1394 (FIREWIRE) Interface (card and cable included), 6-pin connector
Minimum Document Size	TWAIN and ISIS drivers; KODAK Capture Software, Lite
Paper Thickness and Weight Feeder	Perfect Page Scanning with iThresholding, Autocrop, Aggressive Crop, Deskew, Electronic Colour Dropout, Halftone Removal, Noise Removal, VRS Compatible
Multi-feed Detection	CCITT Group IV; JPEG or uncompressed output
Connectivity	JPEG (for colour and greyscale images) TIFF (for bitonal images)
Bundled Software	Standard: 12 months, on-site. Extended: 3 year, on-site option
Imaging Features (in the scanner)	100-240 V; 50-60Hz ENERGY STAR qualified scanners Mercury-free Xenon lamps Operating temperature: 15-30°C
On-board compression	Operating humidity: 15% to 76% RH
File Format Outputs	Standby mode: <38.2 dB(A) Operating mode: <53.8 dB(A) Minimum: PENTIUM III 1 GHz processor, 256 MB RAM
Warranty	Recommended: PENTIUM IV 2.4 GHz processor, 512 MB RAM
Electrical Requirements	WINDOWS 98SE, Me, 2000, XP
Environmental Factors	UL 60950 2000-1, C-UL CAN/CSA-C22.2 No. 60950-1-03, TUV EN 60950-1:2001, CE Mark, 47 CFR Part 15 Subpart B (FCC) Class B, ICES-003 Issue 3 Class B, EN 55022:98 Class B, EN 61000-3-2 Powerline Harmonics, EN 61000-3-3 Flicker, EN 55024, AS/NZS C137.2 Class B (C-Tick Mark), CNS 13438 Class B, VCCI Class B, CISPR 22 Class B Feed Module, Separator Module, Calibration Targets, Feeder Consumables Kit, Extra-Large Feeder Consumables Kit Replaceable imaging guides
Acoustical Noise (operator position Sound Pressure level)	White imaging background accessory
PC Configuration	
Supported Operating Systems	
Approvals and Product Certifications	
Consumables Available	
Accessories	

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.

For more information visit: [www.kodak.com/go/scanners](http://www.kodak.com/go/scanners)



We're here for you.  
Kodak Service & Support

- Weight i150: 8.9 kg  
i160: 10.4 kg
- Depth: 30.0 cm
- Width: 54.7 cm
- Height i150: 23.6 cm  
i160: 36.5 cm



Innovation you can count on™

**datacomIT.**

Information Technology Solutions

Phone Australia wide:

1300 887 507

[www.datacomit.com.au](http://www.datacomit.com.au)